



Delo[®] Syn-AMT XV

Premium performance fully synthetic transmission fluid (Supersedes Multigear MTF HD)

Product description

Delo Syn-AMT XV is a range of premium performance fully synthetic transmission fluids, designed for extended drain service in heavy duty synchronised manual truck transmissions.

Delo Syn-AMT XV lubricants are formulated with fully synthetic base oils in combination with a premium performance additive system, available in viscosity grades SAE 75W-80 and SAE 75W-90.

Customer benefits

- Long-drain capability of 450,000 km or more, reducing the need for transmission overhauls and maintenance downtime
- Designed for low-temperature fluidity, allowing fast circulation and wear protection during cold start-up
- High Viscosity Index and good shear stability help provide viscosity and film thickness sufficient for effective high temperature lubrication throughout fluid service life
- Specially tuned, durable friction characteristics, offer smooth shifting across fluid lifetime
- Proven fuel economy compared to conventional fluids (up to 3% improvement, when used in combination with Delo Syn-Gear HD SAE 75W-90 in the drive axles)
- Durable extreme pressure (EP) protection, designed to resist component scuffing and wear



Product highlights

- **Designed for 450,000 km long-drain capability**
- **Offers cold start protection**
- **Formulated for smooth shifting**
- **Designed for consistent high temperature protection**
- **Offers improved fuel economy**
- **Aids rust, corrosion and wear resistance**

Selected specification standards include:

API	DAF
Daimler	Eaton
MAN	Volvo
ZF	

Applications

Delo Syn-AMT XV is designed for extended drain in heavy duty synchronised manual truck transmissions. In addition to its formal OEM approvals, field trial data demonstrates its potential capability for extended drain in a range of other truck applications. Field trial vehicles include those manufactured by MAN, Mercedes, Scania and Volvo; transmissions include those manufactured by the truck constructors themselves and by ZF, including AS Tronic models and models fitted with intarders.

(Note that ZF mandates the use of a product with a formal TE-ML 01E/02E approval during the warranty period of transmissions with “TE-ML 01” or “TE-ML 02” entries on the type plate. Delo Syn-AMT XV SAE 75W-80 may be used in these applications after the end of the warranty period.)

The SAE 75W-90 viscosity grade is intended principally for conditions of high ambient temperature and/or high operating load, or where the application calls specifically for an SAE 75W-90 viscosity grade product.

Approvals, performance and recommendations

Approvals		75W-80	75W-90
• Eaton	Synthetic (500,000 km/3 years)	X	—
• MAN	341 Type E4	X ^[1]	—
• Volvo	97305	X	—
• Volvo	97307	X	—
• Volvo	97318	X ^[2]	—
Performance		75W-80	75W-90
• API	GL-4	X ^[3]	X
• DAF	Gearbox oil for Eaton gearboxes	X	—
• Volvo	97315-80	—	X
• Volvo	97319	—	X

Recommendations		75W-80	75W-90
• Daimler	MB 235.4	X	—
• Daimler	MB 235.41	X	—
• Daimler	MB 235.11	X ^[4]	X
• MAN	341 Type Z4	X	—
• ZF	TE-ML 02L	X ^[5]	—

^[1] MAN approval number: TUC 0540/12

^[2] Volvo approval number: 03

^[3] Although this product is suitable for use in applications where a GL-4 fluid is specified, it should be noted that the GL-4 specification does not fully address the requirements of synchronized manual transmissions. This fluid is optimised around the needs of commercial vehicle transmissions, and may not give satisfactory performance in applications such as passenger car transmissions

^[4] In transmissions. The SAE 75W-80 viscosity grade has not been validated in transfer cases

^[5] Field trial testing demonstrates suitability for use for up to 400,000 km/3 years

Typical test data			
Test	Test Methods	Results	
Viscosity Grade		75W-80	75W-90
Shelf Life: 60 months from date of filling indicated on the product label			
Density, 15°C, kg/L	ASTM D1298	0.8645	0.859
Flash Point COC, °C	ASTM D92	244	252
Pour Point, °C	ASTM D5950	-54	-48
Viscosity, Kinematic, 100°C, mm ² /s	ASTM D445	9.17	17.03
Viscosity, Kinematic, 40°C, mm ² /s	ASTM D445	54.1	119.6
Viscosity, Brookfield, -26°C, mPa.s	ASTM D2983	3670	—
Viscosity, Brookfield, -40°C, mPa.s	ASTM D2983	19,300	95,000
Viscosity Index	ASTM D2270	151	156

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product